


PRODUCT FEATURES

MONODELTA is a single flap smoke vent suitable for the removal of large quantities of warm air and / or smoke from a building within a short period of time, dayly ventilation and natural lighting. Suitable for utilization on shed style roofs.

The vents are manufactured according to ISO 9001 quality control standards and comply with the European requirements for NSHE according to EN 12101-2. Endurance tests with 10,000 opening and closing cycles have proven its robust and functional design. The vents are formed from high quality corrosion resistant aluminium to ensure low maintenance requirements and watertightness.

Various methods of operation using pneumatic or electric actuators are available. Available on large dimensions, up to 1250 x 3000 mm (width x length).





monodelta

TYPICAL APPLICATIONS

Shed style roofs: 15/15, 30/30, 45/45.

MATERIALS

Tempered aluminium, sea water and corrosion resistant (EN AW 5754).
Corrosion resistant bearings.

Sealant applied so that there is no freezing, enabling the equipment to have low air permeability at the same time.

Note: aluminum is supplied untreated as standard. Possibility of being supplied with electrostatic painting (in any RAL color).

DIMENSIONS

Roof opening width: 500 - 1250 mm.

Roof opening length: 1000 - 3000 mm.

OPENING ANGLE

Open angle from 0° up to 85°.

CONTROLS NATURAL VENTILATION

P2: double pipe compressed air operation.

M230V: electric motor.


CONTROLS FIRE VENTILATION

P2F: double pipe compressed air operation with fire function.

M24V: electric motor.


FLAPS

AL Single aluminium.
AL ISO Double insulated aluminium (ISO thickness 20 and 50 mm).
PC16 Polycarbonate 16 mm, clear or opal.
PC25 Polycarbonate 25 mm, clear or opal.
PC32 Polycarbonate 32 mm, clear or opal.
TB Thermal break in the aluminium profiles. Available for flaps of AL ISO, PC25 mm, PC32 mm.

**BASES**


Single aluminium.
 Double wall aluminium with insulation.
 Double wall aluminium with insulation and TB, thermal break in the aluminium base.

Note: other non-standard bases available upon request.



FLANGES

S1 Flange for single glass.
S2 Flange for double glass.
S3 Flange for roofs, 45° bended.
S4 Flange for roofs and facades.
S5 Flange for upstand, 90° bended downwards.
S6 Flange 90° bended upwards
SLS Flange for skylight connection, for different polycarbonate thicknesses.
SC Flange for connection with other flange (vents connection). Male or female connection.
SCM Flange for male connection.
SCF Flange for female connection.



WEIGHT

Depends on dimensions and type of infill.

OPTIONS


Custom dimensions.
 Powder-coated design (any RAL colour).
 Bird or insect mesh.
 Anti-fall grid 1200 J.

REGULATIONS


The system has been tested and is certified in accordance with EN 12101-2
 Tested in accordance with the Directive 2014/34/EU, DELTA is ATEX certified equipment.

DIMENSIONS


WIDTH	500 up to 850	851 up to 1250
STROKE	575 mm	800 mm
PNEUMATIC CYLINDER	PVZ 40-00	PVZ 40-00
	-	PVZ 50-00
ELECTRIC MOTOR 2A	JM - DC3 900N	JM - DC3 900N
ELECTRIC MOTOR 4A	JM - DC3 1600N	JM - DC3 1600N




TOP VIEW CLOSED




SIDE VIEW CLOSED




FRONT VIEW CLOSED




SECTION S1




SECTION S2




SECTION S3




TOP VIEW



TOP VIEW



SECTION S4



TOP VIEW

SECTION S4